

Guard Urethane Fortified RT - Guard

Description

Superior to conventional Guard products all new technology providing improved surface wear performance with exceptional gloss and safety standards for polish hard surfaces including granite stone & concrete.

Intended Use

New advanced chemical technology to protect polish concrete from chemical stains superior gloss and resistance to abrasion from heavy traffic conditions.

Product Features

• Gloss	Excellent
Durability	Exceptional
• Water/Detergent Resistance	Excellent
• Leveling	Superior

Physical Properties

	•
•	• Solids 12%
•	PH 8.56-9.5
•	Viscosity ,cpsN/A
•	Specific Gravity 1.02
•	• Weight/Gallon(LBS) 8.95
•	Appearance Off-White Emulsion
•	Freeze/Thaw Stability Do Not Freeze

Limitations

Commercial Use Only

Surface Preparation

Prior to applying this product, remove all previous materials and surface soil rinse thoroughly with clear water an allow the surface to dry.

Mixing Instructions

No mixing is required.

Application Instructions

Apply with a clean microfiber pad pour the guard on the surface and apply a thin even coat to allow for adequate time for the coat to dry. A second coat is recommended for optimal performance, it is also recommended to burnish after the second coat is dry.







Guard Urethane Fortified RT - Guard

Note

Guard coverage is approximately 3500 SQFT per gallon on polish concrete surface.

Storage

Do not store above 100F also protect from freezing.

Compliances

Carb compliant less than 1% VOC

Chemical Resistance

Results after one-hour dry time of the following chemicals

- Coffee...... 10
- Red Wine...... 10
- Pickle Brine...... 10
- Vinegar..... 10
- Phosphoric Acid...... 10

Scale Rating = 1-10 Worse - 10 Best

Precautions

Please refer to the appropriate material safety data sheet (MSDS) prior to using this product. For technical assistance, please call 833-693-7699 FOR INDUSTRIAL / PROFESSIONAL USE ONLY KEEP OUT OF REACH OF CHILDREN