

Concrete Sealer Densifier

RT - Densifier

Description

Bright Plus is a unique blend of silicates & surfactants providing superior results that penetrate concrete surfaces that chemically react to increase surface density durability & abrasion resistance.

Intended Use

Interior & Exterior
Extend the useful life of Concrete.
Low-Cost Concrete Treatment
Reduce Permeability & Increase Hardness
Abrasion & Scuff Resistance
Optimizes Gloss

Physical Properties

- Flash Point..... None
- Viscosity 34 CP
- Color..... Clear
- Type of Solids.....Silicates Proprietary

Surface Preparation

Should not be applied to any surface that has already been treated with compounds that might prevent penetration of the silicate or that interfere with the conversion of free lime. Before any concrete is treated the surface must be cleaned. Remove all loose soil and debris with a broom or dust mop. Apply 150 degreaser at 8oz to gallon scrub thoroughly & rinse with clear water. It is recommended to repeat these steps to ensure all contaminants are removed from the surface. For best penetration it is recommended to wait 24 hours for the surface to dry.

Mixing Instructions

Ready to use.

Application Instructions

For diamond polishing after 200 grit apply Diamond Bright Plus with pump sprayer or pour directly on the surface and spread evenly with a flat microfiber pad. Apply at the rate 250 Gallon per sq ft when dry proceed to polish with 400 grit diamonds and repeat the application of Diamond Bright Plus when dry polish with 800 grit diamonds. You may choose to continue polishing to 3000 grit however it is not necessary.

Product Features

Improves Chemical Resistance
Penetrates to provide long term performance.
Once dry insoluble
Forms a stable <High Ratio>, <Low Viscosity> solution.
Improved Coefficient of Friction

Limited Uses

Commercial Use Only

Concrete Sealer Densifier

RT - Densifier

Storage

Containers must be sealed. Store in cool dry place above 40 F away from water, heat & open flames. Provide adequate ventilation. Disposal according to local regulations

Compliances

VOC Less than 25gm/L

Chemical Resistance

N/A

Precautions

Please refer to the appropriate safety data sheet prior to using this product. For technical assistance call customer service at 833-693-7699 Other Notes: Keep containers closed when not in use and upright to prevent leaking DO NOT take internally. Wash hands after using and before eating. Keep Out of Reach of Children